



Application Notes

AutoBlend Systems BioFuels Processing

Advantages

- Technology proven within the petrochemical industries.
- Packages skid-mounted to economize on foot print areas and height restrictions.
- High accuracy metering and leak-free operation.
- Reduced operating costs through use of easy maintenance products.
- Pumps combined with mixing solutions provide the correct blend both for batch and continuous operations.
- Product traceability.
- Energy savings from power-efficient pumps.
- Hazardous Area Compliance to NEMA, NFPA and UL or CSA as needed, and ATEX.



4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX Tel.: 01.39.97.65.10 / Fax.: 01.39.97.68.48 Demande de prix / e-mail : service-commercial@motralec.com

Process

BioDiesel processing is essentially about reducing the viscosity of the virgin or waste oil. This process separates out the Methyl Esters (BioDiesel). The BioDiesel is then washed, and can be blended with performance improving additives and/or compatible PetroDiesel.

The Problem

Production of consistent quality Biofuel from a variety of virgin and waste oils safely, and the flexibility to accurately blend BioFuel with additives and other mineral fuels to produce a variety of end products.

The Solution

AutoBlend BioFuel System can provide the complete solution using Bran+Luebbe ProCam and NOVADOS pumps for accurate ingredient addition, Lightnin Top Entry Mixers for effective tank mixing, and Plenty TRIRO pumps for mixing with PetroDiesel.

AutoBlend BioFuel systems range from simple manually operated single pump packages through to fully automated batching and mixing plant and are custom built to meet the end user's requirements.

Components

Customized packages can be designed for 250 gallon pilot plants to volumes in excess of 50,000 gallons.

Simplified process diagram







