BARNES®

motralec

4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX Tel. : 01.39.97.65.10 / Fax. : 01.39.97.68.48 Demande de prix / e-mail : service-commercial@motralec.com WWW.MOtralec.com

brands you trust.



Barnes Omni Grind[™] centrifugal grinder pump sets a standard for reliability and durability. It is ideal for lowcost, residential or commercial high-head on high-flow applications. The built-in automatic resetting motor overload ensures peace of mind and provides utmost protection. The design allows for easy and trouble-free installation with these features:

- 1. Internal mounted starting components
- 2. Exclusive Quick-Connect Power Cord
- 3. Removable discharge flange

Omni Grind[™] Advantages

- Recessed vortex impeller design easily handles finely ground solids generated by the grinder
- Exclusive Slicerator eliminates jams by applying the full torque of the motor on one small section of the cutter ring at a time

Reduced Life-cycle Costs

- Heavy-duty 2 hp motor with oil lubricated upper and lower ball bearing standard for minimal wear
- Heavy-duty industrial silicon carbide seal for extended usage
- Large pump end bearing and short shaft overhang significantly extends mechanical seal life by reducing shaft deflection
- Reliable Solid Start Switch provides longer life-cycle and improves mean time between service calls
- Oil-filled motor enables the pump motor to run cooler under severe operating conditions

Higher Flow Version: Capacities to 55 GPM Heads to 104 Feet

Higher Head Version: Capacities to 33 GPM Heads to 125 Feet



Accessory Options:

Pump Support Stand

slide rail fitting

• Break Away Fitting or moveable

ESPS[™] (Environmentally Sealed

Pressure Switch) Level Controls

Exclusive Slicerator[™]

The staggered slicing action of the grinder radial cutterdramatically increases the torque at the cutting surface, cuts with less horsepower, and increases

the unit's efficiency. Eliminates clogging with particularly troublesome objects such as plastic, rubber, sanitary napkins, disposable diapers and cloth items.







Omni Grind Features

- 1. Quick disconnect cord
- 2. Threaded discharge flange
- 3. Exclusive Slicerator
- 4. Integral capacitors for start and run
- 5. Oil filled motor with overload protection
- 6. Silicon carbide mechanical seal for long life
- 7. Vortex impeller for solids handling





© 2012 Crane Pumps & Systems, Inc. A Crane Co. Company Printed in U.S.A. BPSOMNI - Rev. D (8/12)

brands you trust.



burks

DEMING®

WEINMAN



