

Graco fuel transfer pumps are designed for long life under demanding conditions!



Fuel Transfer Pumps

Available in 12 or 24 VDC and 115 or 230 VAC

Features & Benefits

- Positive displacement, self priming gear pump
- UL Listed for gasoline, diesel fuel, kerosene and fuel oil (260000)
- Motors are designed for 30-minute duty cycle
- Built-in relief valve and strainer
- Low current draw
- High output flow up to 12 gpm (45 lpm)
- Die cast aluminum construction is lightweight and corrosion resistant
- Factory lubricated bearings for longer life
- Designed for versatile installation on all tank designs including "L" shaped tanks
- Designed for easy servicing without disconnecting any electrical connections



Graco® fuel pumps come complete with 12 ft (3.6 m) hose, nozzle, suction tube and installation hardware

motralec

4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX

Tel. : 01.39.97.65.10 / Fax. : 01.39.97.68.48

Demande de prix / e-mail : service-commercial@motralec.com

www.motralec.com

PROVEN QUALITY. LEADING TECHNOLOGY.



Technical Specifications

Part No	260000	260020	260025	260022
Voltage	12 VDC	24 VDC	115 VAC	230 VAC
Inlet port	1 npt	1 npt	1 npt	1 npt
Outlet port	3/4 npt	3/4 npt	3/4 npt	3/4 npt
Power cord	18 ft	18 ft	N/A	N/A
Hose	3/4 in x 12 ft	3/4 in x 12 ft	3/4 in x 12 ft	3/4 in x 12 ft
Max pressure	10 psi (0.7 bar)	10 psi (0.7 bar)	10 psi (0.7 bar)	10 psi (0.7 bar)
Suction tube	1 in x 34 in	1 in x 34 in	1 in x 34 in	1 in x 34 in
Weight	20 lbs (9 kg)	20 lbs (9 kg)	20 lbs (9 kg)	20 lbs (9 kg)
Instruction manual	311304	311304	311304	311304

Fuel Meters

Graco fuel meters give trouble-free service for measuring the delivery of gasoline, kerosene and diesel fuel. Meters may be mounted on a Graco transfer pump for fast, efficient fueling of your equipment.

Features & Benefits

- Cast aluminum construction for corrosion resistance
- Lightweight and compact design
- Factory calibrated for diesel fuel
- Large, easy-to-read display
- 99.9 gallon or liter resettable counter
- 9999.9 gallon or liter totalizer
- 4 to 20 gpm range (15 to 75 lpm)
- 50 psi (3.5 bar) maximum
- Instruction manual 311309



Ordering Information

260405 Fuel Meter (U.S.)

Displays in gallons.
3/4 npt inlet and outlet ports

260414 Fuel Meter (Metric)

Displays in liters.
3/4 npt inlet and outlet ports

motralec

4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX
Tel. : 01.39.97.65.10 / Fax. : 01.39.97.68.48
Demande de prix / e-mail : service-commercial@motralec.com
www.motralec.com

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.