

DÉSENFUMAGE

selection

VENTILATEURS DE DÉSENFUMAGE

Gamme	Débit (m³/h)																	Extraction	Roue à action	Roue à réaction	Transmission	Accoup. direct	Version isolée				
	100	400	500	700	1 000	2 000	3 500	4 000	6 500	8 000	12 000	14 000	17 500	20 000	25 000	26 000	34 000							40 000	55 000	60 000	70 000
TOURELLES																											
TEDH/TEDVF400					50 à 800 Pa																						
TCDH/TCDV F400					50 à 800 Pa																						
CTHT F400									50 à 900 Pa																		
TOURELLES AXIALES																											
HGHT-V								0 à 1200 Pa																			
CAISSONS																											
KUBAIR F400					50 à 750 Pa																						
KDTA F400 BP		100 à 500 Pa																									
KDTR F400 BP		50 à 500 Pa																									
KDTA F400						120 à 1500 Pa																					
KDTR F400						240 à 2000 Pa																					
MOTO-VENTILATEURS																											
GTLF1 F400					100 à 900 Pa																						
GTLB1 F400					50 à 1800 Pa																						
GTLF3 F400						70 à 1500 Pa																					
GTLB3 F400					50 à 2500 Pa																						
VENTILATEURS AXIAUX																											
THGT F200								50 à 2200 Pa, Ø 400 à 1600																			
THGT F400								50 à 2200 Pa, Ø 400 à 1600																			
TGT								50 à 2200 Pa, Ø 400 à 1600																			
TJHT								Ø 315 à 630																			
CAISSONS AXIAUX																											
CHGT F400								50 à 900 Pa, Ø 400 à 1250																			