



ITT

motralec

4 rue Lavoisier · ZA Lavoisier · 95223 HERBLAY CEDEX
 Tél. : 01.39.97.65.10 / Fax. : 01.39.97.68.48
 Demande de prix / E-mail : service-commercial@motralec.com
 www.motralec.com

Lowara

General Catalogue

QDRMC2 Series

Single-phase electric panels for the protection and control of two single-phase drainage pumps with external capacitor.

SPECIFICATIONS

Automatic control through electromechanical floats

Supply voltage: 1 x 230 V $\pm 10\%$

Frequency: 50/60 Hz

Power: 0.75 to 2.2 kW

Direct motor starting

Protection: IP54

Ambient temperature: -5 to +40 °C

(limit specified by EN standard 60439-1)

Maximum relative humidity: 50% at +40°C provided that no condensation occurs (limit specified by EN standard 60439-1)

Wall mounted

Plastic enclosure

Electronic board with power, overload, high-level alarm, pump on/off indicator lights

Alarm reset button

Run and start capacitor in panel

/TS version with stator thermal protection circuit

/WD version with water control probe in oil bath and stator thermal protection

OPTIONAL ACCESSORIES

- Audible or visual signalling device, 12 Vdc 0.3 A max. (inside the electric panel there are two connection terminals) for high-level alarm
- VR1 single-phase module for overvoltage protection (lightning protector)
- Signal relay board kit (power, aut/man, on/off, overload, high level)



For proper electric panel-electric pump selection, make sure that the Ampere input of the motor falls within the rated current range shown in the table.

Engineered for life




ITT

Lowara

General Catalogue

QDRMC2 SERIES



7

PANEL TYPE	RATED VOLTAGE V	RATED POWER		RATED CURRENT			DIMENSIONS			WEIGHT Kg	C μF	Cs μF
		kW	HP	A	÷	A	A mm	B mm	C mm			
QDRMC2/07	1 x 230 V ± 10 %	0,75	1	4	÷	6,3	390	470	130	8,5	20	40
QDRMC2/15	1 x 230 V ± 10 %	1,5	2	6,3	÷	10	390	470	130	8,5	35	60
QDRMC2/22	1 x 230 V ± 10 %	2,2	3	10	÷	16	390	470	130	8,5	35	60
QDRMC2/07/TS	1 x 230 V ± 10 %	0,75	1	4	÷	6,3	390	470	130	9	20	40
QDRMC2/15/TS	1 x 230 V ± 10 %	1,5	2	6,3	÷	10	390	470	130	9	35	60
QDRMC2/22/TS	1 x 230 V ± 10 %	2,2	3	10	÷	16	390	470	130	9	35	60
QDRMC2/07/WD	1 x 230 V ± 10 %	0,75	1	4	÷	6,3	390	470	130	10	20	40
QDRMC2/15/WD	1 x 230 V ± 10 %	1,5	2	6,3	÷	10	390	470	130	10	35	60
QDRMC2/22/WD	1 x 230 V ± 10 %	2,2	3	10	÷	16	390	470	130	10	35	60

C = Run capacitor; Cs = Start capacitor

CB-QDRMC2_c_te

Engineered for life

motralec

4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX
Tel. : 01.39.97.65.10 / Fax. : 01.39.97.68.48
Demande de prix / E-mail : service-commercial@motralec.com
www.motralec.com

Besoin d'un prix ou d'un conseil technique ?

Coffret électrique Lowara QDRMC2



4,7/5 . +600 avis Google

- Devis rapide et conseil technique par nos spécialistes
- Plus de 200 000 références et 30 marques distribuées
- Vente, réparation, bobinage et SAV en atelier
- Livraison partout en France, accompagnement avant et après-vente

Voir la gamme Lowara sur notre site :

www.motralec.com/.../lowara

DEMANDER UN PRIX >