

C-ATEX-ZAmotbasicEx IE3

Rated power P_N kW	Type	Article no.	Motor size	Motor efficiency η_{mot} %	Rated current I_N A	Rated speed n_N rpm	Maximum speed n_{max} rpm	Maximum frequency f_{max} Hz
1.5	ER35C-4DY.D7.1R	130595/EX41	090L/S	85.5	3.21	1445	2485	86
2.2	ER35C-2DY.D7.1R	130596/EX41	090L/S	86.3	4.43	2870	2980	52
3.0	ER35C-2DY.E7.1R	130597/EX41	100L	87.3	5.77	2910	3320	57
4.0	ER35C-2DY.F7.1R	130598/EX41	112M	88.4	7.59	2900	3650	63

P_N kW	Type	Weight kg	T mm	T1 mm	T3 mm	T4 mm	H2 mm	Flexible connector	Guard grille	Vibration damper		Frequency inverters 3~
										Spring	Rubber	
1.5	ER35C-4DY.D7.1R	65.00	562	579	368	115	535	00406432	00412702	02021198	00090144	308230
2.2	ER35C-2DY.D7.1R	68.00	562	579	368	115	535	00406432	00412702	02021198	00090144	308232
3.0	ER35C-2DY.E7.1R	75.00	562	623	420	115	548	00406432	00412702	02021198	00090144	308234
4.0	ER35C-2DY.F7.1R	96.00	562	641	420	115	561	00406432	00412702	02021199	00090144	308236

Information

ZAbuefin

Cpro

C

C-ATEX

Impellers with hub

System components

Control technology

General notes

