

Fiche produit Motralec Ziehl Abegg FSDM A AQ - fiche technique | Motralec

■ **DEMANDE DE PRIX RAPIDE** : <https://www.motralec.com/demandeContact>

Frequency inverters www.motralec.com / service-commercial@motralec.com / 01.39.97.65.10 Control technology Main catalogue

Frequency inverters

3~ Icontrol Basic, speed controller with display, main switch optional



The Icontrol frequency inverters are intended for requirement-based and energy saving speed control of internal rotor motors (IEC standard motors).

The Icontrol Basic inverters are available as speed controllers in the version with integrated display and main switch.

The speed setting can be made by a master control by 0 – 10 V, e.g. by a ZIEHL-ABEGG control module of the UNIcon product series. The speed can also be set manually by connecting a potentiometer. Two-stage operation with adjustable speeds is also possible optionally.


The 3~ Icontrol Basic inverters are universally suitable for many different applications: E.g. air conditioning, general ventilation tasks, combination with medium pressure axial fans MAXvent.

Input for sensors or speed settings through



Setting of the desired speed through device or by external default, e.g. 0...10 V

Connection diagram



Interference emission according to EN 61000-6-3 (domestic)
Interference immunity according to EN 61000-6-2 (industrial)

Equipment/properties

LC multi-function display with plain text display:

Setting of desired values: Speeds, motor parameters Display of modulation, operating states etc.

1 analog input for speed setting:

Analog input E1: Setting by jumper to desired setting signal: 0-10 V, 0-20 mA or PWM

1 digital input:

D1 - 24 V: Enable function On/Off

1 potential-free fault indication contact:

The contact drops out in case of a fault. Max. load 250 V, 2 A.

Integrated motor protection function:

Connection possibility for thermostats "TB" or thermistors "TP".

Optional version with integrated main switch:

Switch settings 0 - I. The main switch can be locked with a padlock in position 0.

Icontrol Basic with display											
3~ 208...480V 50/60Hz											
Type	Article no.	Rated voltage	Rated current	Rated temperature	Rated power	Max. line fuse	Max. heat dissipation	Maximum ambient temperature	Protection class	Weight	Dimensions (W x H x D)
		V	A	°C	kW	A	W	°C		kg	mm
FSDM2.6A	308228	400	2.6	50	1.1	6	40	55	IP54	2.70	240 x 284 x 115
FSDM3.6A	308230		3.6	40	1.5	6	55	55		2.80	240 x 284 x 115
FSDM5A	308232		5	55	2.2	10	80	55		4.80	250 x 302 x 195.5
FSDM7A	308234		7	50	3	10	105	55		4.90	250 x 302 x 195.5
FSDM8.5A	308236		8.5	55	4	10	130	55		5.80	250 x 302 x 195.5
FSDM12A	308265		12	55	5.5	16	175	55		5.90	250 x 302 x 195.5
FSDM17A	308267		17	50	7.5	20	260	55		6.10	250 x 302 x 195.5
FSDM25A	308323		25	40	11	35	480	55		12.50	280 x 355 x 239
FSDM32A	308325		32	50	15	35	750	55		24.50	386 x 525 x 283
FSDM39A	308327		39	55	18.5	50	900	55		26.30	386 x 525 x 283
FSDM46A	308329		46	50	22	50	1050	55		26.30	386 x 525 x 283
FSDM62A	308331		62	40	30	63	1250	55		26.30	386 x 525 x 283

Devices with a rated temperature below 55 °C can be used up to 55 °C with a reduction in performance
rated power = power rating of the internal rotor motor. The motor rated current is decisive for the assignment of the frequency inverter.

Icontrol Basic with display and main switch											
3~ 208...480V 50/60Hz											
Type	Article no.	Rated voltage	Rated current	Rated temperature	Rated power	Max. line fuse	Max. heat dissipation	Maximum ambient temperature	Protection class	Weight	Dimensions (W x H x D)
		V	A	°C	kW	A	W	°C		kg	mm
FSDM2.6AQ	308229	400	2.6	50	1.1	6	40	55	IP54	2.90	240 x 284 x 149
FSDM3.6AQ	308231		3.6	40	1.5	6	55	55		3.00	240 x 284 x 149
FSDM5AQ	308233		5	55	2.2	10	80	55		5.00	250 x 302 x 229.5
FSDM7AQ	308235		7	50	3	10	105	55		5.10	250 x 302 x 229.5
FSDM8.5AQ	308237		8.5	55	4	10	130	55		6.00	250 x 302 x 229.5
FSDM12AQ	308266		12	55	5.5	16	175	55		6.10	250 x 302 x 229.5
FSDM17AQ	308268		17	50	7.5	20	260	55		6.20	250 x 302 x 229.5
FSDM25AQ	308332		25	40	11	35	480	55		12.80	280 x 355 x 273
FSDM32AQ	308333		32	50	15	35	750	55		25.30	386 x 525 x 317
FSDM39AQ	308334		39	55	18.5	50	900	55		27.10	386 x 525 x 317
FSDM46AQ	308335		46	50	22	50	1050	55		27.10	386 x 525 x 317
FSDM62AQ	308336		62	40	30	63	1250	55		27.10	386 x 525 x 317

Devices with a rated temperature below 55 °C can be used up to 55 °C with a reduction in performance
rated power = power rating of the internal rotor motor. The motor rated current is decisive for the assignment of the frequency inverter.

ziehl-abegg.com



57

Fiche produit Motralec Ziehl Abegg FSDM A AQ - fiche technique | Motralec

■ **DEMANDE DE PRIX RAPIDE** : <https://www.motralec.com/demandeContact>

Besoin d'un prix ou d'un conseil technique ?

Ventilateur Ziehl Abegg FSDM AQ



4,7/5 . +600 avis Google

- Devis rapide et conseil technique par nos spécialistes
- Plus de 200 000 références et 30 marques distribuées
- Vente, réparation, bobinage et SAV en atelier
- Livraison partout en France, accompagnement avant et après-vente

Voir la gamme Ziehl Abegg sur notre site :

www.motralec.com/.../ziehl-abegg

DEMANDER UN PRIX >