





**AELY /
AELIA N**
PORTABLE UNITS
3 Cooling models
From 2,99 kW to 3,5 kW
1 Heat Pump model
Of 4,59 kW



PRODUCT ADVANTAGES

- Monobloc portable units (AELY 9/12) or split portable units (AELIA 14).
- No specific installation is required.
- High dehumidification capacity.
- 3 fan speed.
- Recycling and filtering of the air.
- 24h timer programmer.
- "I feel" function.
- Infrared remote control.



| | | AELY 9 | AELY 12 | AELIA N 10 CDQC | AELIA N 14 IR RCQC |
|-----------------------------------|----------------------------------|-------------------------------|------------------|------------------------|---------------------------|
| Cooling | Capacity | 2.99 | 3.50 | 3.02 | 4.17 |
| | Input power | 1.13 | 1.45 | 0.98 | 1.54 |
| | EER/Energy Label | 2.64 / A | 2.41 / B | 3.1 / A | 2.7 / A |
| | Operating limits | °C 21°/46° Dry Bulb | 21°/46° Dry Bulb | 21°/46° Dry Bulb | 21°/46° Dry Bulb |
| Heating | Capacity | - | - | - | 4.59 |
| | Input power | - | - | - | 1.39 |
| | EER/Energy Label | - | - | - | 3.3/A |
| Indoor unit | Type | Monobloc | Monobloc | Split System | Split System |
| | Sound pressure level 1 mt' dB(A) | 49/51/55 | 61/61,5/62,5 | 43/46/48 | 48/50/51 |
| | Airflow ¹ | m ³ /h 280/310/350 | 470/520/570 | 335/451/503 | 356/401/433 |
| | Dehumidification | l/h 1.4 | 2.2 | 1.25 | 1.80 |
| | Compressor type | Rotary | Rotary | - | - |
| | Dimensions (WxDxH) | mm 450x370x840 | 546x405x840 | 470x360x800 | 470x360x800 |
| | Weight | kg 31 | 47 | 33 | 38 |
| Outdoor unit | Compressor type | - | - | Rotary | Rotary |
| | Dimensions (WxDxH) | mm - | - | 440x320x540 | 440x320x540 |
| | Weight | kg - | - | 17 | 17 |
| | Linking pipes - Lenght | m - | - | 3 | 3 |
| Max. height difference | m - | - | 1.6 | 1.6 | |
| Power supply 1-230V - 50Hz | Part number | 7MB021046 | 7MB021044 | 7MB021032 | 7MB021040 |
| | Price | € | | | |

¹Data are relative to Low speed, Medium speed and High speed