

GRUPPI DI SOLLEVAMENTO CON INVERTER INVERTER CONTROLLED BOOSTER SETS

CPS 10 R2U

Temperatura del liquido: -15° C a +120° C

Grado di protezione: IP55

Classe d'isolamento: F

Pressione max d'esercizio: 16 bar

Liquid temperature: -15° C to +120° C

Protection class: IP55

Insulation class: F

Max operating pressure: 16 bar



motralec

4 rue Lavoisier . ZA Lavoisier . 95223 HERBLAY CEDEX
Tel. : 01.39.97.65.10 / Fax. : 01.39.97.68.48
Demande de prix / e-mail : service-commercial@motralec.com
www.motralec.com

COD.	MOD.	Avviamento Starting	Kw	Prestazioni / Performances		H - max
				Q = m ³ /h	H = metri meters	
UI500400	CPS10-VLR2B/60 R2U	Frequenza variabile Variable frequency	0,75	0,6 - 3,6	56 - 23	57
UI500410	CPS10-VLR2B/110 R2U	Frequenza variabile Variable frequency	1,1	0,6 - 3,6	100 - 43	101
UI500420	CPS10-VLR4/60 R2U	Frequenza variabile Variable frequency	1,1	2,4 - 7,8	53 - 20	55
UI500430	CPS10-VLR4/80 R2U	Frequenza variabile Variable frequency	1,5	2,4 - 7,8	71 - 30	75